



PROJECTEUR MURAL LED 150W

PR150WMCEE – 3700 619 436 173



IP65

ULR

< 3%



CONS :150W



13500 LM

90lm/w

Efficacité lumineuse

LED

SOURCE REMPLACABLE



230V~50Hz



3000K



90°



ORIENTABLE



10M



CLASS I

231 x276
x30mm

IRC

>80

IK

8

CE

Conforme à l'arrêté du 27 décembre 2018 relatif à la prévention, à la réduction des nuisances lumineuses

Cerf/Test report	Directive	Normes
EMC	2014/30/EU	• EN IEC 55015 : 2019 + A11 : 2020 • EN IEC 61000-3-2 : 2019 • EN 61000-3-3 : 2013 + A1 : 2019 • EN 61547 : 2009
LVD	2014/35/EU	• EN IEC 60598-1 : 2021 • EN 60598-2-5:2015 • EN62493:2015 • EN 62471:2008
RoHS	2011/65/EU	

Facteur de puissance > 0.9
Durée de vie : 25 000H
3000K – Blanc CHAUD
Source lumineuse remplaçable
Aluminium / PC cover

Pour un ULR conforme à l'arrêté il convient de ne pas dépasser une inclinaison de 25° par rapport à l'horizontale

CEE Fiches : RES-EC-104 (A14-1) prorogée depuis 2021 Dec.
Rénovation d'éclairage extérieur

YANTEC SAS

92 boulevard Victor Hugo, Bâtiment GH 92110 Clichy FRANCE
Tél : +33 (0)1.34.07.14.14. – Fax : +33 (0)1.44.02.24.35 – www.xanlite.com
SIRET : 390 995 462 00038 – NAF : 4690Z – TVA : FR 73 480 283 654

